


# Peripheral / Communications Cards

## PCI-3488

High-performance IEEE488.2 GPIB Interface Card

- Fully compatible with IEEE 488.2 standard
- Support a 32-bit 3.3V or 5V PCI bus
- Dual 1Kbytes FIFO for read/write operations
- Provide NI-like driver API & VISA support
- Interactive utility for testing and diagnostics



## PCI-A340

Dual ports CRT/DVI Graphic PCI Card


- NVIDIA GeForce FX 5200 Graphic Processor Chip
- Resolutions up to and including 2048x1536@85Hz
- DVD and HDTV-ready MPEG-2 decoding up to 1920x1080i resolutions
- DDR SDRAM 64MB Video RAM, Memory clock 400 MHz
- OS Support Microsoft® Windows® NT/2000/XP, Support DirectX, OpenGL 1.5
- PCI-A340: shipped with Y-shape cable for dual DB-15 VGA channels
- PCI-A340D: shipped with Y-shape cable for dual DVI channels



## PCI-8248

Quad Intel® 82546EB Gigabit Ethernet Ports PCI-X Card with Bypass Function

- Quad Gigabit Ethernet Ports
- Support PCI-X up to 133MHz
- Bypass capability when system power-off or software halt
- Software programmable bypass control
- Programmable watchdog timer, WDT status read-back
- Intel Boot Agent BIOS
- Low-profile bracket is available for OEM programs



## C584

Industry Intelligent 4-port Serial Communication Card

- PCI Rev 2.1 plug and play
- 4 RS-232 serial communications ports
- Supports up to 2 cards per system and Jumperless, easy to configure
- Supports Windows NT/95/98/2000/XP and Linux operation system
- C584/9: Ship with DB-37 to four DB-9 cable



## PCI-8246

Dual Intel® 82546EB Gigabit Ethernet Ports PCI-X Card with Bypass Function

- Dual Gigabit Ethernet Ports
- Support PCI-X up to 133MHz
- Bypass capability when system power-off or software halt
- Software programmable bypass control
- Programmable watchdog timer, WDT status read-back
- Intel Boot Agent BIOS
- Low-profile bracket is available for OEM programs



## C588

Industry Intelligent 8-port Serial Communication Card

- PCI Rev 2.1 plug and play
- 8 RS-232 serial communication ports
- Supports up to 2 cards per system and Jumperless, easy to configure
- Supports Windows NT/95/98/2000/XP and Linux operation system
- C588/9: Ship with DB-68 to eight DB-9 cable



## PCI-8213/8214

Quad/Dual Intel® 82559 10/100Mbps Ethernet 64-bit/66MHz PCI Cards

- 32/64 bits, 33/66MHz PCI bus
- Four/Two Intel 82559 high performance 10/100-BaseTX Ethernet controllers
- Built-in watch-dog timer for bypass feature, which can bypass the Ethernet ports while no-power or system fault automatically (PCI-8214)
- Supports IEEE 802.3u auto-negotiation for 10Base-T /100Base-TX
- Supports IEEE 802.3x 100Base-TX flow control
- Reserved extra pin-header for LAN status LED for panel-free design
- Driver supporting Windows 95/98/NT/2000/XP, Linux



PCI-8213

## C422

Isolated 2-port RS-422/485 Communication Card

- PCI Rev 2.1 plug and play
- 2 serial communications ports with intelligent buffer
- Isolated RS-422 or RS-485 interface
- Supports up to 2 cards per system
- Supports Windows NT/95/98/2000/XP and Linux operation system



## PCI-7841

Dual-port Isolated CAN Interface Card

- Two independent CAN network operation
- Up to 1Mbps programmable transfer rate
- 16MHz CAN controller frequency
- 2500Vrms isolation protection
- Direct memory mapping to the CAN controllers
- Powerful master interface for CAN bus protocols
- PCI bus plug and play
- DOS libraries and Windows DLLs (95, 98, NT, 2000, XP)



## C485

Isolated 4-port RS-422/485 Communication Card

- PCI Rev 2.1 plug and play
- 4 serial communications ports with intelligent buffer
- Isolated RS-422 or RS-485 interface
- Supports up to 2 cards per system
- Supports Windows NT/95/98/2000/XP and Linux operation system
- C485/9: Ship with DB-37 to four DB-9 cable

